

31 30m10
sidewall surface of said large-diameter contact hole excluding said funnel-shaped portion, to a position which is lower than a lower end of said funnel-shaped portion by a predetermined distance, a wiring conductor layer being deposited on said insulator film to cover a top surface of said plug of said refractory conductive material and to fill at least in part space remaining in said large-diameter contact hole thereby to cover a bottom of said large-diameter contact hole and a surface of said sidewall of said refractory conductive material within said large-diameter contact hole, and to cover a surface of said funnel-shaped portion of said large-diameter contact hole.

32
20. (Amended) A semiconductor device including both a large-diameter contact hole and a small-diameter contact hole formed to penetrate through an insulator film formed on a semiconductor substrate to reach said semiconductor substrate, each of said large-diameter contact hole and said small-diameter contact hole having a funnel-shaped portion formed on an upper portion thereof to open or spread upward, said small-diameter contact hole being completely filled with a plug of a refractory conductive material which contacts said semiconductor substrate, and said large-diameter contact hole being partly filled by said refractory conductive material which covers a sidewall surface of said large-diameter contact hole excluding said funnel-shaped portion, to a position which is lower than a lower end of said funnel-shaped portion by a predetermined distance, said refractory conductive material covering said sidewall surface of said large-diameter contact hole having a thickness on a lower portion of said hole, equal to about half the diameter of the small-diameter contact hole, a wiring conductor layer being deposited on said insulator film to cover a top surface of said plug of said refractory conductive material and to fill at least in part space remaining in said large-diameter contact hole thereby to cover a bottom of said large-diameter contact hole and a surface of said sidewall of

HAYES SOLOWAY P.C.
130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7623
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567

92
said refractory conductive material within said large-diameter contact hole, and to cover a surface of said funnel-shaped portion of said large-diameter contact hole.

Kindly add new claims 29-46, to read as follows:

92
--29. A semiconductor device including both a large-diameter contact hole and a small-diameter contact hole formed to penetrate through an insulator film formed on a semiconductor substrate to reach said semiconductor substrate, said small-diameter contact hole being completely filled with a plug of a refractory conductive material, said plug contacting said semiconductor substrate, and said large-diameter contact hole being partly filled by said refractory conductive material which covers a sidewall surface of said large-diameter contact hole, a wiring conductor layer being deposited on said insulator film to cover a top surface of said plug of said refractory conductive material and to contact said semiconductor substrate and a surface of said sidewall of said refractory conductive material within said large-diameter contact hole.

30. A semiconductor device claimed in Claim 29, wherein said refractory conductive material is a material selected from the group consisting of a refractory metal and a silicide of a refractory metal.

31. A semiconductor device claimed in Claim 29, wherein said large-diameter contact hole has an aspect ratio of not greater than 2, and said small-diameter contact hole has an aspect ratio of greater than 2.

32. A semiconductor device claimed in Claim 31, wherein said predetermined distance is in the range of not less than 10% but not greater than 40% of a thickness of said insulator film.

HAYES SOLOWAY P.C.
130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7628
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567

33. A semiconductor device claimed in Claim 29, wherein said predetermined distance is in the range of not less than 10% but not greater than 40% of a thickness of said insulator film.

34. A semiconductor device claimed in Claim 29, wherein said refractory conductive material is a material selected from the group consisting of a refractory metal and a silicide of a refractory metal.

35. A semiconductor device claimed in Claim 34, wherein said large-diameter contact hole has an aspect ratio of not greater than 2, and said small-diameter contact hole has an aspect ratio of greater than 2.

36. A semiconductor device claimed in Claim 35, wherein said predetermined distance is in the range of not less than 10% but not greater than 40% of a thickness of said insulator film.

37. A semiconductor device claimed in Claim 34, wherein said predetermined distance is in the range of not less than 10% but not greater than 40% of a thickness of said insulator film.

38. A semiconductor device including both a large-diameter contact hole and a small-diameter contact hole formed to penetrate through an insulator film formed on a semiconductor substrate to reach said semiconductor substrate, said small-diameter contact hole being completely filled with a plug of a refractory conductive material, which contacts said semiconductor substrate, and said large-diameter contact hole being partly filled by said refractory conductive material, said refractory conductive material covering said sidewall surface of said large-diameter contact hole having a thickness on a lower portion of said hole, equal to about half the diameter of the small-diameter contact hole, a wiring conductor layer being

HAYES SOLOWAY P.C.

130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7623
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567

deposited on said insulator film to cover a top surface of said plug of said refractory conductive material and to fill at least in part space remaining in said large-diameter contact hole thereby to contact said semiconductor substrate.

39. A semiconductor device claimed in Claim 38, wherein said refractory conductive material is a material selected from the group consisting of a refractory metal and a silicide of a refractory metal.

40. A semiconductor device claimed in Claim 38, wherein said large-diameter contact hole has an aspect ratio of not greater than 2, and said small-diameter contact hole has an aspect ratio of greater than 2.

41. A semiconductor device claimed in Claim 40, wherein said predetermined distance is in the range of not less than 10% but not greater than 40% of a thickness of said insulator film.

42. A semiconductor device claimed in Claim 38, wherein said predetermined distance is in the range of not less than 10% but not greater than 40% of a thickness of said insulator film.

43. A semiconductor device claimed in Claim 38, wherein said refractory conductive material is a material selected from the group consisting of a refractory metal and a silicide of a refractory metal.

44. A semiconductor device claimed in Claim 43, wherein said large-diameter contact hole has an aspect ratio of not greater than 2, and said small-diameter contact hole has an aspect ratio of greater than 2.

HAYES SOLOWAY P.C.

130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7623
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567